

HOP-HQ80

Thermal Label Printer



Specifications:

- Thermal printing method, No need ribbon, No need ink
- Support serial sequence and Logo image
- Support 1D 2D bar code printing
- Command: TSPL-EZ emulation, ZPL, EPL, DPL
- Paper width: 20mm-78mm
- Paper roll diameter: 40mm-80mm (Inner roll diameter 1.5inch/40mm), printer warehouse max diameter is 80mm
- High Speed 127 mm/s
- Resolution: 203DPI
- Saw tooth wave easy for tearing paper
- Support Dlabel, Nicelabel, Hilabel etc. software

Data sheet:

Resolution	203 DPI
Print Method	Thermal Print
Print Speed(Max)	127 mm (5") / s,
Print Width(Max)	78mm (3")
Print Length(Max)	1770 mm (70")
Printer Size	145 mm (D) x195 mm (W) x135 mm (H)
Printer Weight	1.2kg
Label Paper Roll Diameter	40-80mm
Paper Direction	Paper Up
Processor	32-bit CPU
Memory	<ul style="list-style-type: none"> ■ 8M Flash memory ■ 8M SDRAM
Interface	USB (Standard) Bluetooth (Optional)
Power	Adaptor <ul style="list-style-type: none"> ■ Input: AC 100-240V ■ Output: DC 24V-2.5A
User Indicator	Standard Model <ul style="list-style-type: none"> ■ 2 Press Buttons ■ 1 LED Blue Light、1 LED Red Light
Sensor	<ul style="list-style-type: none"> ■ Gap Sensor ■ Cover Opening Sensor ■ Printer Head Temperature Sensor
Paper Type	Thermal paper, Thermal adhesive paper, etc
Media Type	Continuous,Gap
Media Width	20 mm ~ 78 mm
Media Thickness	0.06 mm ~ 0.25 mm
Label Length	10 mm ~ 1770 mm
Paper off type	Tear off & peel off
Gap Height	Minimum 2 mm

Print out deviation	Vertical: 1 mm maximum. Horizontal: 1 mm maximum.
Internal font	<ul style="list-style-type: none"> ■ 1 set of alphanumeric fonts
Code Page	<ul style="list-style-type: none"> ■ Codepage 437 (English - US) ■ Codepage 737 (Greek) ■ Codepage 850 (Latin-1) ■ Codepage 852 (Latin-2) ■ Codepage 855 (Cyrillic) ■ Codepage 857 (Turkish) ■ Codepage 860 (Portuguese) ■ Codepage 861 (Icelandic) ■ Codepage 862 (Hebrew) ■ Codepage 863 (French Canadian) ■ Codepage 864 (Arabic) ■ Codepage 865 (Nordic) ■ Codepage 866 (Russian) ■ Codepage 869 (Greek 2) ■ Codepage 950 (Traditional Chinese) ■ Codepage 936 (Simplified Chinese) ■ Codepage 932 (Japanese) ■ Codepage 949 (Korean) ■ Codepage 1250 (Latin-2) ■ Codepage 1251 (Cyrillic) ■ Codepage 1252 (Latin-1) ■ Codepage 1253 (Greek) ■ Codepage 1254 (Turkish) ■ Codepage 1255 (Hebrew) ■ Codepage 1256 (Arabic) ■ Codepage 1257 (Baltic) ■ Codepage 1258 (Vietnam) ■ ISO-8859-1: Latin-1 (Western European) ■ ISO-8859-2: Latin-2 (Central European) ■ ISO-8859-3: Latin-3 (South European) ■ ISO-8859-4: Latin-4 (North European) ■ ISO-8859-5: Cyrillic ■ ISO-8859-6: Arabic ■ ISO-8859-7: Greek ■ ISO-8859-7: Hebrew ■ ISO-8859-9: Turkish ■ ISO-8859-10: Nordic ■ ISO-8859-15: Latin-9 ■ UTF-8
Bar Code	<p>1D bar code Code128 subsets A.B.C, Code128UCC, EAN128, Interleave 2 of 5, Code 39, Code 93, EAN-13, EAN-8, Codabar, POSTNET, UPC-A, UPC-E, EAN and UPC 2(5) digits, MSI, PLESSEY, China Post, ITF14, EAN14, Code 11, TELPEN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS</p> <p>2D bar code CODABLOCK F mode, DataMatrix, Maxicode, PDF-417, Aztec, MicroPDF417, QR code, RSS Barcode (GS1 Databar)</p>

Rotation on font and Bar code	0°, 90°, 180°, 270°
Command	TSPL-EZ emulation,ZPL,EPL,DPL
Environment	Operation Environment: -10 ~ 50 °C (14 ~ 122 °F), Humidity:10 ~ 90% No condensing Storage Environment: -40 ~ 60 °C (-40 ~ 140 °F), Humidity:10 ~ 90% No condensing
Accessories	<ul style="list-style-type: none"> ■ CD (Windows label editing software, Driver and User Manual) ■ Fast installation guide ■ Power adaptor ■ Power cable ■ USB cable
Reliability	<ul style="list-style-type: none"> ■ One year warranty ■ Printer head 50KM or One year warranty. Depends on which reach first. ■ Printer roller 50KM or One year warranty. Depends on which reach first.