

HOP-H801 Thermal Receipt Printer



Product description:

HOP-H801 is a high-end and well-designed thermal receipt printer. 300MM/S high-speed printing. It has an oil-proof cover to ensure excellent waterproof, oil-proof and dust-proof performance; It has front LED lights to remind you of the incoming orders, paper lacking, error notice etc in noisy environments; It has a paper detection function for untaken bill by flashing lights and alarming sound; Printer has a wire cable hidden slot and wall hanging function. Rich interface optional: USB, Ethernet, RS232, Bluetooth, WIFI. Large input buffer, to avoid losing any bills. Hoin Leading technology brings you a high-quality and stable printing experience.

Product performance:

- 300 mm / second ultra high-speed printing, improve the printing efficiency
- Front LED lights remind you of incoming orders, paper lacking, error notice etc.
- Paper detection function for untaken bill by flashing lights and alarming sound
- Excellent waterproof, anti-oil, anti-dust structure design
- Wire cable hidden slot can avoid the damage which comes from splashing oil or splashing water
- Support wall hanging function, meet the special environment printing
- Movable baffle design, support 80MM, 58MM different width of the paper roll printing
- Support kitchen printing and Internet printing
- Using 100M Ethernet card, connect printer faster, to avoid losing bills
- Recover printing after network disconnection, to avoid losing bills
- Support LOGO Graphical download and print
- Support 1D, 2D bar code printing
- Support order come remind and error alarm
- Support Multi language printing
- Compatible with ESC/POS print instruction mode
- Support Windows, Linux, Android and IOS system printing

Printer Parameters:

Item		Parameters
Print Parameters	Printing Method	Thermal Line
	Printing width	72mm
	Resolution	576 Dots/Line or 512 Dots/Line (8dots/mm, 203dpi)
	Print speed	300mm/Second(MAX)
	Interface	USB,Ethernet,RS232,Bluetooth,WIFI(Optional)
	Line Spacing	3.75mm (Can adjust line spacing by command)
	Line No.	FontA-48Lines/FontB-64Lines/Simple,traditional Chinese-24 lines
	Character	Standard GB18030 simplified / traditional Chinese Fonts
	Character Size	ANK character, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots) Simplified/Traditional Chinese: 3.0×3.0mm(24×24 dots)
Bar code Character	Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/Thai/Vietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
	Bar code	1D bar code: UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/CODABAR/CODE93/CODE128 2D barcode: QRCODE
Graphics Printing		Supports bitmap download and print
Paper	Type	Thermal
	Width	79.5±0.5mm
	Diameter	≤80mm
	Feed method	Easy feed(Clameshell feed)
Print Commands		ESC/POS
Oil-proof cover		Support
Bill untaken detection and reminder		Support
Cable hidden slot		Support
Front LED light		Support
Power	Power Adaptor	Input: AC 100V-220V,50-60Hz Output: DC 24V/2.5A
	Cash Drawer output	DC 24V/1A
Physical Characteristics	Weight	1.5KG
	Dimension	195*145*143(MM)
environment	Working	Temp: 5 ~ 45℃, Humidity: 10 ~ 80%
	Storage	Temp: -10 ~ 50℃, Humidity: 10 ~ 90% (No dew)
Reliability parameter	Print Head Life	150KM (print density≤12.5)
	Cutter Life	1500,000times
Software	Driver	Android,IOS,Linux,Windows